

# TKC 80 TKMC 80 SERIES

CLOSED  
OPENABLE TOP AND BOTTOM

VERTICAL AND HORIZONTAL  
DIVIDERS + CLIPS

STANDARD FLANGES or  
METAL PLASTIC



	A	C	KR	P	M/M	PS-KG/M	
MODEL TKC 80/95	139	95	150-200-250 300-400-500	110,86	9,02	6,47	
MODEL TKC 80/125	169	125		...	...	6,98	
MODEL TKC 80/150	194	150		...	...	7,41	
MODEL TKC 80/175	219	175		...	...	7,83	
MODEL TKC 80/200	244	200		...	...	8,26	
MODEL TKC 80/250	294	250		...	...	9,11	
MODEL TKC 80/300	344	300		...	...	9,96	

STROKE LENGTH	SEE PAGE	14
CABLE CARRIER LENGTH	SEE PAGE	14
SELF-BEARING LENGTH IN RELATION TO ADDITIONAL WEIGHT	SEE PAGE	14-15
NON-STANDARD or SPECIAL FLANGES	SEE PAGE	11
LOCKING ELEMENTS	SEE PAGE	12
ASSEMBLY VARIANTS	SEE PAGE	9-10
FOR OTHER TECHNICAL DATA: <b>MODEL TTK80</b>	SEE PAGE	32

S = 22

A = (C1 + C2 + C3) + (S x N. of Bands)

A<sub>MAX</sub> = 2000

N. of bands selectable.

